

## MasterFlow 648 PART C

Version 1.0      Revision Date: 09/11/2020      SDS Number: 000000261491      Date of last issue: -  
Date of first issue: 09/11/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterFlow 648 PART C  
Product code : 000000000050380503 000000000050380503

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Admixtures US,LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585 USA: +1-800-255-3924 Contract  
Number MIS9240420

**Recommended use of the chemical and restrictions on use**


Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Carcinogenicity (Inhalation) : 1A  
Specific target organ toxicity : 3  
- single exposure  
Specific target organ toxicity : Category 1  
- repeated exposure (Inhalation)  
Specific target organ toxicity : 2 (Kidney, Immune system)  
- repeated exposure (Inhalation)

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H335 May cause respiratory irritation.  
H350 May cause cancer.  
H372 Causes damage to organs through prolonged or repeated exposure if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P271 Use only outdoors or in a well-ventilated area.

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

P260 Do not breathe dust or mist.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P270 Do not eat, drink or smoke when using this product.  
 P264 Wash face, hands and any exposed skin thoroughly after handling.

**Response:**

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
 P314 Get medical advice/ attention if you feel unwell.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

No data available.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : inorganic compounds

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 25 - < 100
Barium sulfate	7727-43-7	>= 10 - < 20
calcium oxide	1305-78-8	>= 0.1 - < 0.2

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
 Under no circumstances should organic solvent be used.  
 If irritation develops, seek medical attention.

In case of eye contact : Flush eyes with water as a precaution.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

---

If swallowed	:	If eye irritation persists, consult a specialist. Induce vomiting immediately and call a physician. Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure if inhaled. May cause damage to organs through prolonged or repeated exposure.
Notes to physician	:	Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Water spray Foam Dry powder Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	harmful vapours nitrogen oxides fumes/smoke carbon black
Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Avoid dust formation. Avoid breathing dust. Ensure adequate ventilation.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
---	---	--

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

- Advice on safe handling : Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Materials to avoid : Segregate from incompatible substances.
- Further information on storage stability : No data available

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA value	2 mg/m <sup>3</sup>	ACGIHTLV
		REL value	2 mg/m <sup>3</sup>	NIOSH
		PEL	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
Barium sulfate	7727-43-7	TWA	5 mg/m <sup>3</sup>	OSHA P0
		TWA value (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIHTLV
		REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000

## MasterFlow 648 PART C

Version  
1.0Revision Date:  
09/11/2020SDS Number:  
000000261491Date of last issue: -  
Date of first issue: 09/11/2020

				(Table Z-1)
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIH TLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

Respiratory protection : Wear respiratory protection if ventilation is inadequate.  
Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

---

Eye protection	:	with the producers of the protective gloves. Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	:	Do not inhale dust/fumes/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	granules
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	neutral (as aqueous suspension)
Melting point	:	No applicable information available.
Boiling point	:	not applicable, solid with a melting temperature over 300 °C
Flash point	:	not applicable
Evaporation rate	:	The product is a non-volatile solid.
Flammability (solid, gas)	:	not flammable
Self-ignition	:	not self-igniting (for a component of this mixture)
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower flammability limit	:	No applicable information available.
Vapor pressure	:	No applicable information available.
Relative vapor density	:	No applicable information available.
Relative density	:	approx. 1.15
Solubility(ies)	:	
Water solubility	:	insoluble (68 °F / 20 °C)
Solubility in other solvents	:	(68 °F / 20 °C)

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

---

	insoluble
Partition coefficient: n-octanol/water	: Study technically not feasible.
Autoignition temperature	: No applicable information available.
Decomposition temperature	: No decomposition if stored and handled as prescribed/indicated.
Viscosity	
Viscosity, dynamic	: Not applicable
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive Not explosive
Oxidizing properties	: Based on its structural properties the product is not classified as oxidizing.
Self-heating substances	: No data available
Sublimation point	: No applicable information available.
Molecular weight	: No data available
Metal corrosion rate	: Corrosive effects to metal are not anticipated.

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: See SDS section 7 - Handling and storage.
Incompatible materials	: Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	: No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity	: Remarks: No applicable information available.
Acute inhalation toxicity	: Remarks: No applicable information available.
Acute dermal toxicity	: Remarks: No applicable information available.

## MasterFlow 648 PART C

Version 1.0      Revision Date: 09/11/2020      SDS Number: 000000261491      Date of last issue: -  
Date of first issue: 09/11/2020

---

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure if inhaled.  
May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

**Persistence and degradability****Product:**

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biode-

---



## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

---

gradable according to OECD classification.

**Bioaccumulative potential****Product:**

Bioaccumulation : Remarks: No data available.  
Discharge into the environment must be avoided.

**Components:****Quartz (SiO<sub>2</sub>):**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Barium sulfate:**

Partition coefficient: n-octanol/water : Pow: 4.26  
log Pow: 0.63  
Method: other (calculated)

**calcium oxide:**

Partition coefficient: n-octanol/water : Remarks: The value has not been determined because the substance is inorganic.

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Ozone-Depletion Potential : Remarks: The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.  
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## MasterFlow 648 PART C

Version 1.0      Revision Date: 09/11/2020      SDS Number: 000000261491      Date of last issue: -  
Date of first issue: 09/11/2020

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

---

**SECTION 15. REGULATORY INFORMATION****US State Regulations****Pennsylvania Right To Know**

Barium sulfate	7727-43-7
Quartz (SiO <sub>2</sub> )	14808-60-7
crystalline silica	14808-60-7

**New Jersey Right To Know**

Quartz (SiO <sub>2</sub> )	14808-60-7
crystalline silica	14808-60-7

**California Prop. 65**

WARNING: This product can expose you to chemicals including Quartz (SiO<sub>2</sub>), which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory


---

**SECTION 16. OTHER INFORMATION****Further information**

## MasterFlow 648 PART C

Version 1.0      Revision Date: 09/11/2020      SDS Number: 000000261491      Date of last issue: -  
Date of first issue: 09/11/2020

## NFPA 704:



## HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1001-1050	: OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1001-1050 / OSHA Action level	: OSHA Action level:
29 CFR 1910.1001-1050 / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA P0 / TWA	: 8-hour time weighted average

## MasterFlow 648 PART C

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

OSHA Z-1 / TWA : 8-hour time weighted average  
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/11/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING

**MasterFlow 648 PART C**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/11/2020	000000261491	Date of first issue: 09/11/2020

---

WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN