SAFETY DATA SHEET

B59LV550

Section 1. Identification

Product name : FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive

Product code : B59LV550

Other means of : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

identification

Manufacturer : Distributed By:

The Sherwin-Williams Co. 101 W. Prospect Avenue Cleveland, OH 44115

Emergency telephone number of the company

: US / Canada: (216) 566-2917

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Product Information Telephone Number

: US / Canada: 1-800-474-3794

Mexico: Not Available

Regulatory Information Telephone Number

: US / Canada: (216) 566-2902

Mexico: Not Available

Transportation Emergency

: US / Canada: (216) 566-2917

Telephone Number

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 1C

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 56.2%

(oral), 72.9% (dermal), 74% (inhalation)

GHS label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Precautionary statements

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 1/14

B59LV550 FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive SHW-85-NA-GHS-US

Section 2. Hazards identification

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage Disposal

: Store locked up.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

WARNING: This product contains a chemical known to the State of California to cause cancer. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	≥50 - ≤75	68953-36-6
1,3,5-Triazine-2,4,6-triamine	≥10 - ≤25	108-78-1
Perlite	≤10	93763-70-3
Silicate Fibers	≤5	287922-11-6
Glass	≤5	65997-17-3
Amide Wax	≤3	-
Tri(dimethylaminomethyl)phenol	≤3	90-72-2
3,6,9-triazaundecamethylenediamine	≤2.5	112-57-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 2/14

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 3/14

B59LV550 FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive SHW-85-NA-GHS-US

Section 4. First aid measures

Ingestion

: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 4/14

B59LV550 FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive

SHW-85-NA-GHS-US

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 5/14

Section 8. Exposure controls/personal protection

Ingredient name	CAS#	Exposure limits
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6	None.
1,3,5-Triazine-2,4,6-triamine	108-78-1	OARS WEEL (United States, 1/2021). TWA: 3 mg/m³ 8 hours.
Perlite	93763-70-3	NIOSH REL (United States, 10/2020). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). [Particulates not otherwise regulated] TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust
Silicate Fibers	287922-11-6	ACGIH TLV (United States, 1/2022). [Aluminum, metal and insoluble compounds] TWA: 1 mg/m³ 8 hours. Form: Respirable fraction
Glass	65997-17-3	NIOSH REL (United States, 10/2020). [FIBROUS GLASS DUST] TWA: 3 f/cc 10 hours. TWA: 5 mg/m³ 10 hours. Form: Total NIOSH REL (United States, 10/2020). [MINERAL WOOL FIBER] TWA: 3 f/cc 10 hours. Form: Fibers of spec length ACGIH TLV (United States, 1/2022). [Continuous filament glass fibers] TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
Amide Wax Tri(dimethylaminomethyl)phenol 3,6,9-triazaundecamethylenediamine	90-72-2 112-57-2	None. None. OARS WEEL (United States, 1/2021). Absorbed through skin. Skin sensitizer. TWA: 5 mg/m³ 8 hours.

Occupational exposure limits (Canada)

Ingredient name	CAS#	Exposure limits
Isomelamine	108-78-1	OARS WEEL (United States, 1/2021). TWA: 3 mg/m³ 8 hours.
Tetraethylenepentamine	112-57-2	OARS WEEL (United States, 1/2021). Absorbed through skin. Skin sensitizer. TWA: 5 mg/m³ 8 hours.

Occupational exposure limits (Mexico)

	CAS#	Exposure limits
None.		

Date of issue/Date of revision: 11/25/2022Date of previous issue: 9/12/2022Version: 226/14B59LV550FIRETEX M90/02 Epoxy Intumescent Coating Blue AdditiveSHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

point, and boiling range

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.

Color : Not available.

Odor : Not available.

Odor threshold : Not available.

PH : Not applicable.

Melting point/freezing point : Not available.

Boiling point, initial boiling : Not available.

CI | 0500 (00005) ID |

Flash point : Closed cup: 95°C (203°F) [Pensky-Martens Closed Cup]

Date of issue/Date of revision: 11/25/2022Date of previous issue: 9/12/2022Version: 227/14B59LV550FIRETEX M90/02 Epoxy Intumescent Coating Blue AdditiveSHW-85-NA-GHS-US

Section 9. Physical and chemical properties

Evaporation rate : Not available.
Flammability : Not available.
Lower and upper explosion : Not available.

limit/flammability limit

Vapor pressure: Not available.Relative vapor density: Not available.

Relative density : 1.17

Solubility(ies)

Not available.

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Molecular weight : Not applicable.

Aerosol product

Heat of combustion : 1.231 kJ/g

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,3,5-Triazine-2,4,6-triamine	LD50 Oral	Rat	3161 mg/kg	-
Tri(dimethylaminomethyl)	LD50 Dermal	Rat	1280 mg/kg	-
phenol				
	LD50 Oral	Rat	1200 mg/kg	-
3,6,9-triazaundecamethylenediamine	LD50 Oral	Rat	3990 mg/kg	-

Irritation/Corrosion

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 8/14

B59LV550 FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive

SHW-85-NA-GHS-US

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3,5-Triazine-2,4,6-triamine	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
Tri(dimethylaminomethyl)	Eyes - Severe irritant	Rabbit	-	24 hours 50	-
phenol	Oldin Milalimitana	D. 4		ug	
	Skin - Mild irritant	Rat	-	0.025 MI	-
	Skin - Severe irritant	Rabbit	-	24 hours 2	-
				mg	
	Skin - Severe irritant	Rat	-	0.25 MI	-
3,6,9-triazaundecamethylenediamine	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	5 mg	-
	Skin - Severe irritant	Rabbit	-	495 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 5	-
				mg	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
1,3,5-Triazine-2,4,6-triamine	-	2B	-
Glass	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision: 11/25/2022Date of previous issue: 9/12/2022Version: 229/14B59LV550FIRETEX M90/02 Epoxy Intumescent Coating Blue AdditiveSHW-85-NA-GHS-US

Section 11. Toxicological information

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	4922.22 mg/kg
Dermal	11585.09 mg/kg

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 10/14

B59LV550 FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive SHW-85-NA-GHS-US

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1,3,5-Triazine-2,4,6-triamine	-	<3.8	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

: 9/12/2022

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN3066	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT. Marine pollutant (Fatty acids, tall-oil, reaction products with tetraethylenepentamine)
Transport hazard class(es)	8	8	8	8	8
Packing group	III	III	III	III	III

Date of issue/Date of revision

: 11/25/2022 Date of previous issue Version: 22

11/14

FIRETEX M90/02 Epoxy Intumescent Coating Blue Additive

No.	No.	No.	Yes. The environmentally hazardous substance mark	Yes.
-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required wher transported in sizes of ≤5 L or ≤ kg. Emergency schedules F-A, S B
ERG No.	ERG No.	ERG No.		
153	153	153		
	- ERG No.	- Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8). ERG No. ERG No.	- Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8). ERG No. ERG No. ERG No.	environmentally hazardous substance mark is not required. - Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8). ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No. ERG No.

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air. etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International regulations

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.


Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Date of issue/Date of revision 12/14 : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1C	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

History

Date of printing : 11/25/2022 Date of issue/Date of : 11/25/2022

revision

Date of previous issue : 9/12/2022

Version : 22

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 13/14

Section 16. Other information

should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 11/25/2022 Date of previous issue : 9/12/2022 Version : 22 14/14