



## SAFETY DATA SHEET

### Protal 7125 Part A Resin

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

#### 1. Identification

##### Product identifier

**Product name** Protal 7125 Part A Resin

**Product number** 6140036R

##### Recommended use of the chemical and restrictions on use

**Application** Industrial use as a protective coating in prevention of corrosion.

**Uses advised against** No specific uses advised against are identified.

##### Details of the supplier of the safety data sheet

**Supplier** See Manufacturer

**Manufacturer** Denso North America  
9710 Telge Road  
Houston, TX 77095  
1 (281) 821-3355  
1 (281) 821-0304  
info@densona.com

##### Emergency telephone number

**Emergency telephone** 1-801-629-0667

#### 2. Hazard(s) identification

##### Classification of the substance or mixture

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Carc. 1B - H350 Repr. 2 - H361d STOT RE 1 - H372

**Environmental hazards** Not Classified

**Supplementary information** The source of the carcinogenic classification is encapsulated within the product mixture. When mixed with Part B, the mixture cures and forms an inert solid and is not considered hazardous.

##### Label elements

##### Hazard symbols



**Signal word**

Danger

## Protal 7125 Part A Resin

### Hazard statements

H226 Flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H350 May cause cancer.  
 H361d Suspected of damaging the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.

### Precautionary statements

P102 Keep out of reach of children.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P234 Keep only in original container.  
 P240 Ground/ bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing gas, fume, vapors or spray.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P263 Avoid contact during pregnancy/ while nursing.  
 P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P284 In case of inadequate ventilation wear respiratory protection.  
 P301+P310 If swallowed: Immediately call a poison center/ doctor.  
 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
 P302+P352 If on skin: Wash with plenty of water.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 If exposed or concerned: Get medical advice/ attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
 P391 Collect spillage.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

Proprietary Resin B, Proprietary Filler B, Proprietary Filler C

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

### Mixtures

## Protal 7125 Part A Resin

<b>Proprietary Resin B</b>	<b>10-30%</b>
CAS number: Proprietary	
<b>Classification</b>	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
Repr. 2 - H361d	
STOT RE 1 - H372	
<b>Proprietary Filler A</b>	<b>10-30%</b>
CAS number: Proprietary	
<b>Classification</b>	
Not Classified	
<b>Proprietary Filler B</b>	<b>10-30%</b>
CAS number: Proprietary	
<b>Classification</b>	
Eye Irrit. 2A - H319	
STOT SE 3 - H335	
STOT RE 2 - H373	
<b>Proprietary Filler C</b>	<b>5-10%</b>
CAS number: Proprietary	
<b>Classification</b>	
Carc. 1B - H350	
STOT RE 1 - H372	
<b>Proprietary Filler E</b>	<b>1-5%</b>
CAS number: Proprietary	
<b>Classification</b>	
Not Classified	
<b>Proprietary Additive A</b>	<b>&lt;1%</b>
CAS number: Proprietary	
<b>Classification</b>	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT RE 2 - H373	
Aquatic Chronic 2 - H411	

## Protal 7125 Part A Resin

<b>Proprietary Solvent B</b>	<b>&lt;1%</b>
CAS number: Proprietary	
<b>Classification</b>	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
STOT SE 1 - H370	

The full text for all hazard statements is displayed in Section 16.

**Ingredient notes** The exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR 1910.1200.

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration. Get medical attention.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. Keep affected person under observation. Get medical attention if symptoms are severe or persist.
<b>Skin Contact</b>	It is important to remove the substance from the skin immediately. Remove contaminated clothing immediately and wash skin with soap and water. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contamination with soap and water or recognized skin cleansing agent. Wash clothing and clean shoes thoroughly before reuse. Get medical attention if symptoms are severe or persist after washing. Following contact with hot product, immediately immerse affected area in, or flush with, large amounts of cold water to dissipate heat and cover with clean cotton sheeting or gauze. Get medical attention. In the event of any sensitization symptoms developing, ensure further exposure is avoided.
<b>Eye contact</b>	Rinse with water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

#### Most important symptoms and effects, both acute and delayed

## Protal 7125 Part A Resin

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Ingestion</b>	May cause irritation. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Skin contact</b>	Redness. Irritating to skin. Prolonged or repeated exposure may cause the following adverse effects: May cause cancer.
<b>Eye contact</b>	Irritating to eyes.

### Indication of immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. Vapors are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Follow precautions for safe handling described in this safety data sheet. Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapors and contact with skin and eyes. Use suitable respiratory protection if ventilation is inadequate.

## Protal 7125 Part A Resin

### Environmental precautions

#### **Environmental precautions**

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

#### **Methods for cleaning up**

Wear protective clothing as described in Section 8 of this safety data sheet. Stop leak if safe to do so. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Use only non-sparking tools. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. The contaminated absorbent may pose the same hazard as the spilled material. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

#### **Reference to other sections**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## 7. Handling and storage

### Precautions for safe handling

#### **Usage precautions**

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin, eyes and clothing. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. May cause cancer. May damage fertility. May damage the unborn child. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

#### **Advice on general occupational hygiene**

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### Conditions for safe storage, including any incompatibilities

#### **Storage precautions**

Store away from incompatible materials (see Section 10). Store locked up. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

#### **Storage class**

Flammable liquid storage.

### Specific end uses(s)

#### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.

## 8. Exposure controls/Personal protection

## Protal 7125 Part A Resin

### Control parameters

### Occupational exposure limits

#### **Proprietary Resin B**

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 85 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 40 ppm 170 mg/m<sup>3</sup>

A4

Long-term exposure limit (8-hour TWA): OSHA 100 ppm

Ceiling exposure limit: OSHA 200 ppm

#### **Proprietary Filler A**

Long-term exposure limit (8-hour TWA): OSHA 20 particles/cc respirable dust

Long-term exposure limit (8-hour TWA): ACGIH 0.1 f/cc containing asbestos fibers

A1

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m<sup>3</sup> respirable fraction

A4

#### **Proprietary Filler C**

Long-term exposure limit (8-hour TWA): OSHA 0.05 mg/m<sup>3</sup> respirable dust

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m<sup>3</sup> respirable fraction

A2

#### **Proprietary Filler E**

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m<sup>3</sup>

A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust

#### **Proprietary Solvent B**

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m<sup>3</sup>

Sk

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 260 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A4 = Not Classifiable as a Human Carcinogen.

A1 = Confirmed Human Carcinogen.

A2 = Suspected Human Carcinogen.

Sk = Danger of cutaneous absorption.

**Ingredient comments**                      No dust formed during normal use.

#### Proprietary Resin B

**Immediate danger to life  
and health**                      700 ppm

#### Proprietary Filler A

**Immediate danger to life  
and health**                      3000 mg/m<sup>3</sup> 3000 mg/m<sup>3</sup>

#### Proprietary Filler C

**Immediate danger to life  
and health**                      25 mg/m<sup>3</sup> 50 mg/m<sup>3</sup>

#### Proprietary Filler E

## Protal 7125 Part A Resin

**Immediate danger to life and health** 5000 mg/m<sup>3</sup>

### Proprietary Solvent B

**Immediate danger to life and health** 6000 ppm

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

##### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

##### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

##### Hygiene measures

Contaminated work clothing should not be allowed out of the workplace. Persons susceptible to allergic reactions should not handle this product. Take off immediately all contaminated clothing and wash it before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Warn cleaning personnel of any hazardous properties of the product.



## Protal 7125 Part A Resin

### Respiratory protection

The use of a respirator is normally not required for outdoor application and areas with adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Do not use in confined spaces without adequate ventilation and/or respirator. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. If dust is generated: Wear a suitable dust mask.

### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Color</b>	White.
<b>Odor</b>	Mild. Irritating.
<b>Odor threshold</b>	Not determined.
<b>pH</b>	~ 7
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	~ 31°C/88°F Tag closed cup.
<b>Evaporation rate</b>	Not applicable.
<b>Evaporation factor</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not determined.
<b>Upper/lower flammability or explosive limits</b>	Not determined.
<b>Other flammability</b>	Not determined.
<b>Vapor pressure</b>	Not determined.
<b>Vapor density</b>	> 1
<b>Relative density</b>	~ 1.52
<b>Bulk density</b>	Not determined.
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	~20,000 cP @ 25°C/77°F
<b>Explosive properties</b>	Not determined.

## Protal 7125 Part A Resin

<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidizing properties</b>	This mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

### 10. Stability and reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidizing agents.
<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
<b>Materials to avoid</b>	Oxidizing materials. Acids - oxidizing.
<b>Hazardous decomposition products</b>	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

### 11. Toxicological information

#### Information on toxicological effects

**Toxicological effects** When mixed with Part B, the mixture cures and forms an inert solid and is not considered hazardous.

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 35,714.29

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 107,142.86

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (vapours mg/l)** 45.63

#### Skin corrosion/irritation

**Animal data** Irritating.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Causes serious eye irritation.

#### Respiratory sensitization

**Respiratory sensitization** Based on available data the classification criteria are not met.

#### Skin sensitization

**Skin sensitization** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

## Protal 7125 Part A Resin

<b>Genotoxicity - in vitro</b>	Based on available data the classification criteria are not met.
<b><u>Carcinogenicity</u></b>	
<b>Summary</b>	Contains a substance which may cause cancer by inhalation. Due to the physical nature of this product, exposure by this route is unlikely. The source of the carcinogenic classification is encapsulated within the product mixture. No dust formed during normal use.
<b>Carcinogenicity</b>	May cause cancer.
<b>IARC carcinogenicity</b>	Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Based on available data the classification criteria are not met.
<b>Reproductive toxicity - development</b>	Suspected of damaging the unborn child.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	Not classified as a specific target organ toxicant after a single exposure.
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	STOT RE 1 - H372
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Based on available data the classification criteria are not met.
<b>General information</b>	
	Avoid contact during pregnancy/while nursing. May damage fertility. Contains a substance which may cause cancer by inhalation. Due to the physical nature of this product, exposure by this route is unlikely. The source of the carcinogenic classification is encapsulated within the product mixture. No dust formed during normal use. May cause cancer after repeated exposure. Risk of cancer depends on duration and level of exposure. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	No specific symptoms known.
<b>Ingestion</b>	May cause irritation.
<b>Skin Contact</b>	Redness. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes.
<b>Route of exposure</b>	Ingestion Inhalation Skin and/or eye contact
<b>Target Organs</b>	No specific target organs known.

### 12. Ecological information

<b>Ecotoxicity</b>	The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. It is unlikely that the substance will dissolve in water in amounts big enough to have a toxic effect on fish and daphnia. However, large or frequent spills may have hazardous effects on the environment. When mixed with Part B, the mixture cures and forms an inert solid and is not considered hazardous.
<b>Toxicity</b>	Based on available data the classification criteria are not met.
<b><u>Persistence and degradability</u></b>	
<b>Persistence and degradability</b>	The degradability of the product is not known.
<b><u>Bioaccumulative potential</u></b>	

## Protal 7125 Part A Resin

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

### Mobility in soil

**Mobility** No data available.

### Other adverse effects

**Other adverse effects** None known.

## 13. Disposal considerations

### Waste treatment methods

#### **General information**

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

#### **Disposal methods**

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

## 14. Transport information

### UN Number

<b>UN No. (TDG)</b>	1263
<b>UN No. (IMDG)</b>	1263
<b>UN No. (ICAO)</b>	1263
<b>UN No. (DOT)</b>	UN1263

### UN proper shipping name

<b>Proper shipping name (TDG)</b>	PAINT
<b>Proper shipping name (IMDG)</b>	PAINT
<b>Proper shipping name (ICAO)</b>	PAINT
<b>Proper shipping name (DOT)</b>	PAINT

### Transport hazard class(es)

<b>DOT hazard class</b>	3
<b>DOT hazard label</b>	3
<b>TDG class</b>	3
<b>TDG label(s)</b>	3
<b>IMDG Class</b>	3
<b>ICAO class/division</b>	3

## Protal 7125 Part A Resin

### Transport labels



### DOT transport labels



### Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

### Environmental hazards

#### Environmentally Hazardous Substance

No.

### Special precautions for user

EmS	F-E, S-E
DOT reportable quantity	RQ: Styrene (4332.6805 lbs), RQ: N,N-Diethylaniline (357142.8571 lbs)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory information

### US Federal Regulations

#### SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

#### CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

##### *Proprietary Solvent B*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

##### *Proprietary Additive B*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

##### *Proprietary Resin B*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

##### *Proprietary Additive A*

Final CERCLA RQ: 1000(454) pounds (Kilograms)

#### SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

#### SARA 313 Emission Reporting

The following ingredients are listed or exempt:

## Protal 7125 Part A Resin

### *Proprietary Solvent B*

1.0 %

### *Proprietary Resin B*

0.1 %

### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

### **SARA (311/312) Hazard Categories**

None of the ingredients are listed or exempt.

### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

### **US State Regulations**

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Filler E*

#### **California Air Toxics "Hot Spots" (A-I)**

The following ingredients are listed or exempt:

*Proprietary Solvent C*

*Proprietary Solvent B*

*Proprietary Resin B*

#### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

#### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Filler A*

*Proprietary Filler B*

*Proprietary Resin B*

#### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Additive B*

*Proprietary Filler A*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

## Protal 7125 Part A Resin

*Proprietary Additive A*

### **Rhode Island "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Filler A*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

### **Minnesota "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Filler A*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

### **New Jersey "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Additive B*

*Proprietary Filler A*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

*Proprietary Additive A*

### **Pennsylvania "Right To Know" List**

The following ingredients are listed or exempt:

*Proprietary Solvent B*

*Proprietary Additive B*

*Proprietary Filler A*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

*Proprietary Additive A*

### **Inventories**

#### **US - TSCA**

The following ingredients are listed or exempt:

*Proprietary Solvent C*

*Proprietary Solvent A*

*Proprietary Solvent B*

*Proprietary Additive B*

## Protal 7125 Part A Resin

*Proprietary Filler A*

*Proprietary Filler D*

*Proprietary Filler C*

*Proprietary Filler E*

*Proprietary Resin B*

*Proprietary Diluent A*

*Proprietary Additive A*

### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### 16. Other information

#### Abbreviations and acronyms used in the safety data sheet

TDG: The transport of dangerous goods act

IATA: International air transport association.

ICAO: Technical instructions for the safe transport of dangerous goods by air.

IMDG: International maritime dangerous goods.

CAS: Chemical abstracts service.

ATE: Acute toxicity estimate.

LC<sub>50</sub>: Lethal concentration to 50 % of a test population.

LD<sub>50</sub>: Lethal dose to 50% of a test population (median lethal dose).

EC<sub>50</sub>: 50% of maximal effective concentration.

PBT: Persistent, bioaccumulative and toxic substance.

vPvB: Very persistent and very bioaccumulative.

#### Classification abbreviations and acronyms

Flam. Liq. = Flammable liquid

Carc. = Carcinogenicity

Eye Irrit. = Eye irritation

Repr. = Reproductive toxicity

Skin Irrit. = Skin irritation

STOT RE = Specific target organ toxicity-repeated exposure

#### Training advice

Only trained personnel should use this material.

#### Issued by

HS&E Manager.

#### Revision date

9/3/2020

#### Revision

2

#### Supersedes date

5/7/2019

#### SDS No.

5224



## Protal 7125 Part A Resin

### Hazard statements in full

H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H301 Toxic if swallowed.  
H311 Toxic in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H350 May cause cancer.  
H361d Suspected of damaging the unborn child.  
H370 Causes damage to organs .  
H372 Causes damage to organs through prolonged or repeated exposure.  
H372 Causes damage to organs (Hearing organs) through prolonged or repeated exposure.  
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.