Safety Data Sheet PREMALUBE

Supercedes Date 04/18/2014

Issuing Date 12/21/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name PREMALUBE Recommended use Lubricant Information on Manufacturer CERTIFIED LABS, DIV. OF NCH CORP. BOX 152170

IRVING, TEXAS 75015

Product Code 10032735 Chemical nature Petroleum oil blend **Emergency Telephone Number** CHEMTREC® 800-424-9300 Telephone inquiry 972-579-2477

2. HAZARD IDENTIFICATION

Color Black

Physical state Grease

Odor Oily

GHS

Classification

Physical Hazards

None

Health Hazard

None

Other hazards

None

Labeling

Signal Word

Not classified

10 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight %	
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5	60-100	
Aluminum benzoate fatty acid complex	82980-54-9	7-13	
Calcium carbonate	471-34-1	7-13	
Molybdenum disulfide	1317-33-5	0.1-1	
Barium dinonylnaphthalene sulfonate	25619-56-1	0.1-1	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice

Avoid contact with skin, eyes and clothing.

Eye Contact

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation

develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and

Inhalation Ingestion If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Notes to physician

Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur.

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point 450 °F / 232 °C

Method Open cup

Flammability Limits in Air %: No information available.

Lower: No data available

Suitable Extinguishing Media

Water spray. Foam. Carbon dioxide (CO2). Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Upper: No data available

Specific hazards arising from the chemical

Material can create slippery conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure -demand, NOHSC (approved or equivalent) and full protective gear.

NFPA

Health 1

Flammability 1

Instability 0

HMIS

Health 1

Flammability 1

Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment. Prevent further leakage or spillage if safe to do so. Material can

create slippery conditions.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment

Contain spillage, soak up with non -combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up

Pick up and transfer to properly labeled containers.

Neutralizing Agent

Not applicable.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing.

Storage

Store in original container. Keep containers tightly closed in a dry, cool and well -ventilated place.

Storage Temperature

Minimum Indoor

10 °F /-12 °C

Maximum Heated

150 °F / 66 °C

Storage Conditions

X

Outdoor

X

Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	TWA: 5 mg/m ³ ; STEL: 10 mg/m ³	TWA: 5 mg/m ³	No data available
Calcium carbonate	No data available	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dus
Molybdenum disulfide	TWA: 10 mg/m ³ inhalable fraction TWA: 3 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust	No data available
Barium dinonylnaphthalene sulfonate	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

General Hygiene Considerations

Eye/Face Protection Skin Protection

Safety glasses with side-shields. For prolonged or repeated contact, use protective gloves with appropriate chemical resistance.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Ensure that eyewash stations and safety showers are close to the workstation location. Remove

and wash contaminated clothing before re -use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Color **Odor Threshold**

рН

Grease Black Not applicable

Viscosity Odor **Appearance Specific Gravity**

Semi-Solid Oily Opaque 0.92

0

0

Evaporation Rate VOC Content (%)

0 (BuAc = 1)0 <0.01 mmHg @ 70°F

Not applicable

Percent Volatile (Volume) VOC Content (g/L) Vapor Density n-Octanol/Water Partition

11.3 (Air = 1.0)No data available No data available

Vapor Pressure Solubility Melting Point/Range Boiling Point/Range

Flash Point

Negligible No data available No data available

450 °F / 232 °C

Decomposition Temperature Flammability (solid, gas) Method

No data available Open cup

Autoignition Temperature Flammability Limits in Air %:

No information available. No information available

Upper: No data available Lower: No data available

10. STABILITY AND REACTIVITY

Chemical Stability Conditions to Avoid Stable. Hazardous polymerization does not occur. Extremes of temperature and direct sunlight, Keep away from open Incompatible Products **Decomposition Temperature Hazardous Decomposition Products**

Possibility of Hazardous Reactions

flames, hot surfaces, and sources of ignition. Strong oxidizing agents, Acids, Bases. No data available Carbon oxides, Sulfur oxides, Oxides of phosphorus, Hydrocarbons, Aldehydes, Ketones. None under normal processing.

11. TOXICOLOGICAL INFORMATION

Product Information

No information available

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50

No information available

Dermal LD50

No information available

Inhalation LC50

Gas Mist Vapor

No information available No information available

No information available

Principle Route of Exposure

Eve contact, Skin contact,

Primary Routes of Entry Acute Effects:

Eye contact.

Eyes Skin

Low hazard for usual industrial or commercial handling. Low hazard for usual industrial or commercial handling.

Inhalation Ingestion

Low hazard for usual industrial or commercial handling. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Toxicity

Prolonged skin contact may defat the skin and produce dermatitis.

Target Organ Effects Aggravated Medical Conditions Respiratory system, Eyes, Skin. Respiratory disorders, Skin disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Petroleum distillates, nydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	No data available	No data available	No data available
Calcium carbonate 471-34-1	= 6450 mg/kg (Rat)	no data available	No data available	No data available	No data available
Molybdenum disulfide 1317-33-5	No data available	no data available	> 2820 mg/m ³ (Rat) 4 h	No data available	No data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Calcium carbonate 471-34-1	No data available	No data available	No data available	No data available	Skin; Eyes; Respiratory system

Carcinogenicity

There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Product Information

No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	Partition coefficien
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Container Disposal Dispose of in accordance with local regulations.

Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Component	CAS No.	Weight %	SARA 313 - Threshold Values
Barium dinonylnaphthalene sulfonate	25619-56-1	0.1-1	1.0

CERCLA

16. OTHER INFORMATION

 Prepared By
 Adrienne McKee

 Supercedes Date
 04/18/2014

 Issuing Date
 12/21/2016

Issuing Date 12/21/2016

Reason for Revision
Glossary
No information available.
List of References.
No information available.
No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.