CRO

SAFETY DATA SHEET

1. Identification

Product identifier Moly-Graph® Extreme Pressure Multi-Purpose Grease - 14 oz

Other means of identification

Product Code No. SL3141 (Item# 1007866)

Recommended use Lubricating grease Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

www.crcindustries.com

Telephone

Website

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

REC)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying. Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	50 - 60
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	30 - 40
calcium bis(dinonylnaphthalenesulphonate)		57855-77-3	0.1 - 1

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreat light naphthenic	ed	64742-53-6	0.1 - 1
graphite		7782-42-5	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste

disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions 7. Handling and storage

Precautions for safe handling Conditions for safe storage, including any incompatibilities Observe good industrial hygiene practices. For product usage instructions, see the product label. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

Components	Туре	Value	Form
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR	1910.1000)		
Components	Туре	Value	
graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit	V alues		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
·	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
ogical limit values	No biological exposure limits noted for		

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Rubber gloves. Latex gloves.

Wear suitable protective clothing. Other

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

> NIOSH-approved cartridge respirator with a particulate cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual

employee exposure levels.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Grease. Color Gray.

Odor Mild petroleum. **Odor threshold** Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

680 °F (360 °C) estimated

275.0 °F (135.0 °C) estimated Flash point

Evaporation rate Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Vapor pressure 45292.3 hPa estimated

> 1 (air = 1) Vapor density

Relative density 0.9

Solubility(ies)

Insoluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available. Not available. Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition No ha

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

InhalationBased on available data, the classification criteria are not met.Skin contactBased on available data, the classification criteria are not met.Eye contactBased on available data, the classification criteria are not met.IngestionBased on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

<u>Acute</u>

Dermal
LD50 Rabbit

> 2000 mg/kg

Oral

LD50 Rat

> 5000 mg/kg

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

<u>Acute</u>

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 2180 mg/m³, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans. (CAS 64742-65-0)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - Not classified.

single exposure

Not diassilica.

Specific target organ toxicity -

Not classified.

repeated exposure

Material name: Moly-Graph® Extreme Pressure Multi-Purpose Grease - 14 oz

No. SL3141 (Item# 1007866) Version #: 01 Issue date: 11-03-2020

Aspiration hazard Not an aspiration hazard.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΔΤΔ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

graphite (CAS 7782-42-5)

US. Massachusetts RTK - Substance List

distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) graphite (CAS 7782-42-5)

US. Pennsylvania Worker and Community Right-to-Know Law

graphite (CAS 7782-42-5)

US. Rhode Island RTK

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) graphite (CAS 7782-42-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

Not determined

Consumer products (40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region

United States & Puerto Rico

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

Yes

On inventory (yes/no)*

16. Other information, including date of preparation or last revision

Issue date 11-03-2020
Prepared by Allison Yoon

Version # 01

DisclaimerThe information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Moly-Graph® Extreme Pressure Multi-Purpose Grease - 14 oz No. SL3141 (Item# 1007866) Version #: 01 Issue date: 11-03-2020