

Date of issue: 16/08/2019 Version: 1.2a

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article

Trade name : ProRox GR 900 – 999, ProRox GS 900 – 999, ProRox LF 900 – 999, ProRox LM 900 – 999,

ProRox MA 500 – 599, ProRox MA 900 – 999, ProRox MA 7000 – 7999, ProRox PS 200 – 299, ProRox PS 600 – 699, ProRox PS 900 – 999, ProRox PSM 900 – 999, ProRox QM 900 – 999, ProRox SL 200 – 299, ProRox SL 400 – 499, ProRox SL 500 – 599, ProRox SL 600 – 699, ProRox SL 900 – 999, ProRox WM 200 - 299, ProRox WM 600 – 699, ProRox WM 900 – 999. SeaRox FB 6000 – 6999, SeaRox FM 6000 – 6999, SeaRox LM 900 – 999, SeaRox MA 700 – 799, SeaRox MA 7000 – 799, SeaRox SL 300 – 399, SeaRox SL 400 – 499, SeaRox SL 600 – 699, SeaRox SL 700 – 799, SeaRox SL 900 – 999, SeaRox WM 600 – 699, SeaRox WM 900

- 999, Aquaduct, Aquaduct CL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : ProRox: Thermal insulation of industrial installations.

SeaRox: Thermal insulation in marine and offshore installations

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rockwool B.V.

Rockwool Technical Insulation

Industrieweg 15

6045 JH Roermond

Netherlands

T: +31 475 35 3915 www.rti.rockwool.com

Producing factories

- Norway (Trondheim and Moss)
- Denmark (Doense and Vamdrup)
- Germany (Neuburg, Flechtingen and Gladbeck)
- Netherlands (Roermond)
- United Kingdom (Pencoed)
- Poland (Cigacice and Malkinia)
- Czech Republic (Bohumin)
- Hungary (Tapolca)
- France (Saint Eloy les Mines)
- Spain (Caparroso)
- Croatia (Potpican)
- Switzerland (Flums)

Or imported by any of these manufacturers from the ROCKWOOL site in Russia (Vyborg) or the ROCKWOOL site in India (Dahej)

1.4. Emergency telephone number

Emergency number : +31 475 35 3915 (business hours GMT+1)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

16/08/2019 EN (English) 1/7



2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

Other hazards not contributing to the classification

other hazards which do not result in classification

: Dust can be generated during cutting or fabrication of the product. When heated to approximately 200 °C for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate the eyes and respiratory system. Further information can be found in section 8.

SECTION 3: Composition/information on ingredients

Substances

Not applicable

Mixtures 3.2.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Man-made vitreous (silicate) fibres with random orientation with alkaline oxide and alkali earth oxide (Na2O+K2O+CaO+MgO+BaO) content greater than 18% by weight and fulfilling one of the note Q conditions	(EC-No.) 926-099-9 (EC Index-No.) 650-016-00-2 (REACH-no) 01-2119472313-44	95 - 100	Not classified
Urea, polymer with formaldehyde and phenol	(CAS-No.) 25104-55-6	2 - 5	Not classified
Residual oils (petroleum), solvent-dewaxed (contains less than 3% DMSO extract)	(CAS-No.) 64742-62-7 (EC-No.) 265-166-0 (EC Index-No.) 649-471-00-X	0.5	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : If exposure symptoms persist, seek medical attention.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact After contact with skin, take off immediately all contaminated clothing, and wash immediately

with plenty of water and soap. Rinse skin with water/shower.

First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Call a physician. First-aid measures after ingestion Rinse mouth immediately and drink plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact : may cause physical irritation upon direct contact.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

: Water spray. carbon dioxide (CO2), dry chemical powder, foam. Suitable extinguishing media

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : The product itself does not burn.

Explosion hazard : not explosive.

Advice for firefighters

Firefighting instructions Use self-contained breathing apparatus when in close proximity to fire. Wear proper protective

equipment.

Protective equipment for firefighters Wear a self contained breathing apparatus. Wear recommended personal protective

equipment.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

16/08/2019 EN (English) 2/7



6.1.1. For non-emergency personnel

Protective equipment : Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. Refer to chapter 8.

6.1.2. For emergency responders

Protective equipment : In case of inadequate ventilation wear respiratory protection. Refer to chapter 8.

Emergency procedures : Stop leak if safe to do so. Evacuate and limit access.

6.2. Environmental precautions

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Refer to sections 8 and 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Spilled material should be removed immediately to avoid formation of dust from dried material.

Sweep up or vacuum up the product.

6.4. Reference to other sections

Refer to sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Unpack material at application site to avoid unnecessary handling of product. Keep work area clean. Collect all waste in suitable and labelled containers and dispose according to local legislation. Wet dust with water before sweeping. Dust must be exhausted directly at the point of origin.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Store tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Residual oils (petroleum), solvent-dewaxed (contains less than 3% DMSO extract) (64742-62-7)		
Latvia	OEL TWA (mg/m³)	5 mg/m³
Poland	NDS (mg/m³)	5 mg/m³
Slovakia	NPHV (priemerná) (mg/m³)	1 mg/m³
Slovakia	NPHV (priemerná) (ppm)	5 ppm
Slovakia	OEL STEL (ppm)	15 ppm
Slovakia	NPHV (Hraničná) (mg/m³)	3 mg/m³
USA - ACGIH	ACGIH TWA (mg/m³)	5 mg/m³

Additional information

: Workplace exposure limit (WEL) must not be exceeded. (total respirable, 8-hour time weighted averages). The dust concentration of inhalable fibres will be under normal working conditions less than 0,1 per cm³.

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation.

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Hand protection:

Wear suitable gloves tested to EN 374.

Eye protection:

tightly fitting safety goggles. DIN EN 166.

Skin and body protection:

Long sleeved protective clothing. Wear work clothes with long sleeves.

16/08/2019 EN (English) 3/7



Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 149. (FFP1)

Further information by the manufacturer: all stone wool insulation products contain a small amount of organic matter which primarily consist of carbon, nitrogen and hydrogen. Depending on the product this can be up to 5 % by weight. During the first heating of the insulation material to temperatures above approx. 200°C this organic matter is decomposed (broken down). During this process some smoke development and / or an irritating smell can be noticed. Incomplete combustion of organic matter does not affect the quality or declared performances of installed products.

The composition of smoke will depend on the actual circumstances at location and will be influenced by the actual temperature, the speed of heating, presence of oxygen etc. The development of smoke and / or irritating smell during the "running in" of the installation can typically last for a period from a few hours up to approximately 4 days. Especially in newly insulated power plants, where temperature is increased gradually until full running conditions are met, this period of time needs to be taken into account. Ventilate the area well and to keep distance to the heated equipment until no further development of smoke or strong irritating smell is noticed.

If an enclosed area (room) where the heating takes place needs to be entered during the "running in" period wear a full face mask with fresh air supply for personal protection.

Other information:

Handle in accordance with good industrial hygiene and safety procedures.



Ventilate working area if possible



Waste should be disposed of according to local regulations



Cover exposed skin. When working in unventilated area wear disposable face mask



Clean area using vacuum equipment



Wear goggles when working overhead



Rinse in cold water before washing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Article. Stone wool.
Colour : Grey. green. Yellow.

Odour : Odourless.

Odour threshold : No data available pH : Not applicable.

Relative evaporation rate (butylacetate=1) : No data available

Melting point : > 1000 °C

Freezing point : No data available
Boiling point : No data available
Flash point : Not applicable
Auto-ignition temperature : No data available

Decomposition temperature : 200 °C

Flammability (solid, gas) : Not flammable
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available

Solubility : Chemically inert substance.
Water: Insoluble in water

Log Pow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : Not explosive.
Oxidising properties : Not applicable.
Explosive limits : Not explosive.

9.2. Other information

No additional information available



SECTION 10: Stability and reactivity

Reactivity

Hazardous polymerisation does not occur.

Chemical stability 10.2.

Stable under normal conditions.

Possibility of hazardous reactions

None under normal conditions.

Conditions to avoid 10.4.

None known.

Incompatible materials 10.5.

Strong acids, bases.

Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO2). When heated to approximately 200 °C for the first time, release of binder components and binder decomposition products can occur which, in high concentrations, may irritate the eyes and respiratory system.

SECTION 11: Toxicological information

Information on toxicological effects 11.1.

Acute toxicity : Not classified

Additional information : No acute toxicity even at high doses.

Urea, polymer with formaldehyde and phenol (25104-55-6)

LD50 oral rat 7 g/kg

Residual oils (petroleum), solvent-dewaxed (contains less than 3% DMSO extract) (64742-62-7)

LD50 dermal rabbit > 2000 mg/kg Skin corrosion/irritation : Not classified pH: Not applicable.

: Not classified

Serious eye damage/irritation pH: Not applicable.

Dust from this product may cause eye irritation

Respiratory or skin sensitisation : Not classified

Additional information May cause slight irritation to the skin

Inhalation of dust may cause irritation of the respiratory system.

symptoms may include stinging, tearing, redness, swelling and blurred vision

Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity Not classified STOT-single exposure : Not classified STOT-repeated exposure : Not classified Aspiration hazard : Not classified

SECTION 12: Ecological information

Toxicity

Additional information

: This product is not hazardous. Ecology - general

12.2. Persistence and degradability

ProRox and SeaRox	
Persistence and degradability	Product is not easily biodegradable.

12.3. **Bioaccumulative potential**

ProRox and SeaRox	
Bioaccumulative potential	No bioaccumulation.

12.4. **Mobility in soil**

ProRox and SeaRox	
Ecology - soil	Not expected to adsorb on soil.

Results of PBT and vPvB assessment

No additional information available

Other adverse effects

Other adverse effects : No information available.

16/08/2019 EN (English) 5/7



SECTION 13: Disposal considerations

Waste treatment methods

Product/Packaging disposal recommendations : Comply with local regulations for disposal.

Additional information Empty containers should be taken for recycling, recovery or waste in accordance with local

regulation.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number	14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippi	ng name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard	class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
not applicable				

14.6. Special precautions for user

Special transport precautions

: Not applicable.

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

Transport in bulk according to Annex II of Marpol and the IBC Code 14.7.

IBC code : not applicable.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. **EU-Regulations**

Contains no substance on the REACH candidate list

15.1.2. **National regulations**

Germany

VwVwS Annex reference : Water hazard class (WGK) nwg, no hazard to waters (Classification according to VwVwS,

Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

: Residual oils (petroleum), solvent-dewaxed (contains less than 3% DMSO extract) is listed : Residual oils (petroleum), solvent-dewaxed (contains less than 3% DMSO extract) is listed

NIET-limitatieve lijst van voor de voortplanting

: None of the components are listed

giftige stoffen - Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Vruchtbaarheid

16/08/2019 EN (English) 6/7



NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

: None of the components are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

The substance is not hazardous

SECTION 16: Other information

Indication of changes:

CAS number has been changed.

Abbreviations and acronyms:

ACGIH (American Conference of Governement Industrial Hygienists)
ASTM - American Society for Testing and Materials
CAS - Chemical Abstracts Service
CLP - Classification, Labelling and Packaging
CSR - Chemical Safety Report
DIN - Deutsches Institut für Normung eV (German Institute for Standardization)
EC - European Community
EEC - European Economic Community
GESTIS: Gefahrstoffdaten banken (Database on hazardous substances)
GHS - Globally Harmonised System
GPPS: general purpose polystyrenes
HCS - Hazard Communication Standard
HMIS - Hazardous Materials Identification System
IARC (International Agency for Research on Cancer)
MSDS - Material Safety Data Sheet
Occupational Safety and Health Administration (OSHA):
OSHA - Occupational Safety and Health Administration
Overland transport (ADR)
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals
UP: Unsaturated polyester
SDS - Safety Data Sheet
VCI - volatile corrosion inhibitor

Other information

: The CAS number under which the Note Q fibres fall is 65997-17-3. Under this number the fibres are registered in the chemical registry systems in most countries in the world. This CAS number however is very broad. The specific chemistry of the bio-soluble fibre has been laid down in the CAS number 287922-11-6 and 1010446-98-6 and can be tracked in the CAS Registry System only.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

16/08/2019 EN (English) 7/7